

Hellerman Tyton SE28 Diesel Resistant Heatshrink



Brand: Competition Systems

Product Code: SE28

Availability: 7 Days

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Price: \$0.00

Short Description

SE28 is used for long-term protection of cables and wire harnesses in military equipment, motor sports and aviation.

Description

Features

- Flexible, high performance elastomeric heat shrink tubing
- Used in aerospace, defence, railway and automotive applications
- Resistant to diesel fuel, aviation and hydrolic fluids
- Provides a reliable protection against abrasion and mechanical damage
- Very suitable for protecting cables and wire harnesses

Specifications

Application Tool	H5002, H5004, E4500
Colour	Black (BK)
Description Short (BMEcat) (max. 150 characters)	Heat Shrinkable Tubing 2:1 VG-Norm 3,2/1,6
GLOBAL PART DESCRIPTION	SE28 3.2/1.6-POA-BK
Marking Text	as per VG
Pack Cont.	150m
Package Quantity per	reel
Printable (Yes/No)	No
Product Family	SE28
Product Group	Heat Shrinkable Tubing 2:1 - Elastomer
Short Description	Diesel resistant shrink tubing
Shrink Ratio	2:1
Variant	Standard-Wall
With inner glue (Yes/No)	No

Material Specifications

Longitudinal Change After Shrinkage	-10 % max.
Recov. ? d max.	1.6mm
Recov. ? d max.	.06"
Supplied ? D min.	3.2mm
Supplied ? D min.	.13"
Wall (WT)	0.8mm
Wall (WT)	.03"

Material and Specifications

Designation as per VG-Norm	VG 95343 T05 D 001 A
Dielectric Strength	24,5 kV/mm
ELV compliant (Article 4 - 2)	YES
Flammability	self-extinguishing
Halogenfree	No

Hazardous good	No
Material	Elastomer, cross-linked (POA)
Min. Shrink Temperature - °C	+170 °C
Operating Temperature - °C	-75 °C to +150 °C
Specifications	NF F 00-608, SAE - AMS - DTL-23053, VG 95343-5:2006-06
Tensile Strength	12MPa